CHI MEI
OPTOELECTRONICS CORP.

Approval

TFT LCD Approval Specification

MODEL NO.: M220Z3-L07

Customer : _____

Approved by : _____

Note :

核准時間	部門	審核	角色	投票
2010-01-11 18:25:42	**MTR** 產品管理處	吳 2010.01.11 柏 勳	Director	Accept

Version 2.3

Doc No.: 400032626
Issued Date: Dec. 31, 2009
Model No.: M220Z3-L07

Approval

- CONTENTS -

Version 2.3

Doc No.: 400032626
Issued Date: Dec. 31, 2009
Model No.: M220Z3-L07

Approval

REVISION HISTORY

Version	Date	Section	Description
Ver 0.0	Mar. 11 '09	All	M220Z3-L07 Tentative Specifications was first issued。
Ver 1.0	June, 02 '09	1.5	Update module weight to (typ) 2030g & (max) 2080g
		2.2.2	Confirm Max. Light Bar Peak pulse current to be 30mA
		2.2.2	Confirm Max. Light Bar input voltage to be 29.7V(typ) & 32.4(max.)
		3.1	Confirm LVDS common input voltage – Min. 1.0V & Max. 1.4V
		3.1	Note(2): update "Power on rush current measurement conditions"
		4.1	Modify the block diagram of TFT LCD module – take away the type of the input connector.
		5.1	Update the description of Pin 25/26/27: become "For LCD internal use only, Do not connect" Modify the description of Note(1), become "Connector Part No.: 093G30-B0001A(STARCONN) or MSAKT2407P30HA (STM)or FI-X30SSLH-HF(JAE)" Add Note(2) Add Note(3)
		6.1	Modify the input signal timing specifications table & its note below the table. Add Note(1) Add Note(2) Add Note(3)
		7.2	Confirm Color Chromaticity: Min.Value = Typ. – 0.03,and Max.Value = Typ. + 0.03 Confirm Min. Center Luminance of White to be 200nits Confirm Min. CR to be 700:1. Confirm Response Time value (TR & TF). Confirm Max. White Variation to be 1.33
		10.0	Add CH 10.0 Reliability Test
		11.4	Add CH 11.4. Storage
		11.5	Add CH 11.5. Operation condition guide
Ver 2.0	July, 08 '09	3.3	Correct CN1 & CN2 FFC type, it should be 91500-01001-H01
		5.1	Correct Note (3), the FFC type should be 91500-01001-H01
		6.2	Modify LVDS Clock Max Frequency become 76MHz, and in Vertical Active Display Term, Max. Frame Rate (Fr) shall be 75Hz & Max. total Tv shall be 1090 Th
Ver 2.1	July, 30 '09	8.2	Modify Figure 8-1
Ver 2.2	Oct., 23 '09	7.2	Modify White Variation from (max.) 1.33 to (max.) 1.43
		2.2	Modify the table & add Note (2)
		3.2	Change to new ver. CH3.2
		3.3	Delete LED: PT01B1XX
		6.2	Modify Note(2) description & Drawing: "Power of Lamp" -> "Power of Backlight".
		7.1	Modify CH7.1 table
		7.2	Modify CH7.2 table – Test Condition & Note (5), because of changing Test Equipment CS-2000.
Ver 2.3	Dec., 31 '09	7.2	Modify Gy (typical) to be 0.617 & Note(3)
		3.1	Modify LVDS differential input voltage(min) to be 200
		3.1	Add Note (5)
		9.1	Modify (c) & (d) YMD(year) Description

Version 2.3

Doc No.: 400032626
Issued Date: Dec. 31, 2009
Model No.: M220Z3-L07

Approval

1. GENERAL DESCRIPTION

1.1 OVERVIEW

The M220Z3-L07 model is a 22 inch wide TFT-LCD slimming module with a WLED light bar Backlight Unit and a 30-pin 2ch-LVDS interface. This module supports 1680 x 1050 WSXGA$^+$ (16:10 wide screen) mode and displays up to 16.7 millions colors. The converter module for the Backlight Unit is not built in.

1.2 FEATURES

- Super wide viewing angle

- High contrast ratio (typical 1,000:1)

- Fast response time

- WSXGA$^+$ (1680 x 1050 pixels) resolution

- DE (Data Enable) only mode

- LVDS (Low Voltage Differential Signaling) interface

- RoHS compliance.

- Lower power consumption

- Halogen Free

1.3 APPLICATION

- Workstation & desktop monitor

- Display terminals for AV application

1.4 GENERAL SPECIFICATI0NS

Item	Specification	Unit	Note
Diagonal size	558.68	mm	
Active Area	473.76x296.1	mm	(1)
Bezel Opening Area	477.7 (H) x 300.1 (V)	mm	
Driver Element	a-Si TFT active matrix	-	-
Pixel Number	1680 x R.G.B. x 1050	pixel	-
Pixel Pitch	0.282(H) x 0.282(V)	mm	-
Pixel Arrangement	RGB vertical stripe	-	-
Display Colors	16.7 millions	color	-
Transmissive Mode	Normally White	-	-
Color saturation	68% NTSC	-	-
Surface Treatment	Hard coating (3H), AG (Haze 25%)	-	-
Module Power Consumption	12.05	Watt	(2)

1.5 MECHANICAL SPECIFICATIONS

Item		Min.	Typ.	Max.	Unit	Note
Module Size	Horizontal(H)	493.2	493.7	494.2	mm	(1)
	Vertical(V)	319.6	320.1	320.6	mm	
	Depth(D)	---	10	10.5	mm	
Weight		---	2030	2080	g	
I/F connector mounting position		The mounting inclination of the connector makes the screen center within ±0.5 mm as the horizontal.				

Note (1) Please refer to the attached drawings for more information of front and back outline dimensions.
Note (2) Please refer to sec.3.1 & 3.2 for more information of power consumption

Version 2.3

Doc No.: 400032626
Issued Date: Dec. 31, 2009
Model No.: M220Z3-L07

Approval

2. ABSOLUTE MAXIMUM RATINGS

2.1 ABSOLUTE RATINGS OF ENVIRONMENT

Item	Symbol	Value		Unit	Note
		Min.	Max.		
Storage Temperature	T_{ST}	-20	+60	ºC	(1)
Operating Ambient Temperature	T_{OP}	0	+50	ºC	(1), (2)
Shock (Non-Operating)	S_{NOP}	-	50	G	(3), (5)
Vibration (Non-Operating)	V_{NOP}	-	1.5	G	(4), (5)
LCD Cell Life Time	L_{CELL}	50,000	-	Hrs	MTBF based

Note (1) Temperature and relative humidity range is shown in the figure below.

(a) 90% RH Max. (Ta $\leqq$ 40 ºC).

(b) Wet-bulb temperature should be 39 ºC Max. (Ta > 40 ºC).

(c) No condensation.

Note (2) The temperature of panel surface should be 0 ºC Min. and 60 ºC Max.

Note (3) 50G, 11 ms, half-sine wave, 1 time for ± X, ± Y, ± Z.

Note (4) 10 ~ 300 Hz, sweep rate 10 min / cycle , 30 min for X,Y,Z axis

Note (5) Upon the Vibration and Shock tests, the fixture used to hold the module must be firm and rigid enough to prevent the module from twisting or bending by the fixture.

5 / 28

Version 2.3

Approval

2.2 ELECTRICAL ABSOLUTE RATINGS

2.2.1 TFT LCD MODULE

Item	Symbol	Value		Unit	Note
		Min.	Max.		
Power Supply Voltage	Vcc	-0.3	6	V	(1)
Logic Input Voltage	Vlogic	-0.3	3.6	V	

2.2.2 BACKLIGHT UNIT

Item	Symbol	Value			Unit	Note
		Min.	Typ.	Max.		
LED Forward Current Per Input Pin	I_F	0	20	30	mA	(1), (2) Duty=100%
LED Reverse Voltage Per Input Pin	V_R	---	---	110	V	
Power Dissipation Per Input Pin	P_D	---	---	4.620	W	

Note (1) Permanent damage to the device may occur if maximum values are exceeded. Function operation

should be restricted to the conditions described under Normal Operating Conditions.

Note (2) Specified values are for input pin of LED light bar at Ta=25±2 ℃ (Refer to 3.2 and 3.3 for further

information).

Version 2.3

Approval

3. ELECTRICAL CHARACTERISTICS

3.1 TFT LCD MODULE
Ta = 25 ± 2 ºC

Parameter		Symbol	Value			Unit	Note
			Min.	Typ.	Max.		
Power Supply Voltage		Vcc	4.5	5.0	5.5	V	-
Ripple Voltage		V_{RP}	-	--	100	mV	-
Rush Current		I_{RUSH}	-	--	5	A	(2)
Power Supply Current	White	Icc	-	560	780	mA	(3)a
	Black		-	950	1330	mA	(3)b
	Vertical Stripe		-	920	1290	mA	(3)c
Power Consumption (without Backlight Unit)		P_{LCD}	-	4.75	6.7	Watt	(4)
LVDS differential input voltage		Vid	200	-	600	mV	-
LVDS common input voltage		Vic	1.0	1.2	1.4	V	-
Logic High Input Voltage		VIH	2.64	3.3	3.5	V	
Logic Low Input Voltage		VIL	-	0	0.66	V	

Note (1) The module is recommended to operate within specification ranges listed above for normal function.

Note (2) Power on rush current measurement conditions:

Vcc rising time is 470µs

Version 2.3

Doc No.: 400032626
Issued Date: Dec. 31, 2009
Model No.: M220Z3-L07

Approval

Note (3) The specified power supply current is under the conditions at Vcc = 5.0 V, Ta = 25 ± 2 ºC, f_v = 60 Hz, whereas a power dissipation check pattern below is displayed.

Note (4) The power consumption is specified at the pattern with the maximum current.

a. White Pattern

Active Area

b. Black Pattern

Active Area

c. Vertical Stripe Pattern

Active Area

Note (5) VID waveform condition

Single-End

Differential Signal

Version 2.3

Approval

3.1.2 Vcc Power Dip Condition:

Dip condition: $4.0V \leq Vcc \leq 4.5V, Td \leq 20ms$

3.2 BACKLIGHT UNIT (LED matrix is 9S12P)   Ta = 25 ± 2 ℃

Parameter	Symbol	Value			Unit	Note
		Min.	Typ.	Max.		
LED Light Bar Input Voltage Per Input Pin	V_{PIN}	30.8	36.3	39.6	V	(1), Duty=100%, I_{PIN}=20mA
LED Light Bar Current Per Input Pin	I_{PIN}	0	20	30	mA	(1), (2) Duty=100%
LED Life Time	L_{LED}	25000	30000	---	Hrs	(3)
Power Consumption	P_{BL}	---	10.164	11.088	W	(1) Duty=100%, I_{PIN}=20mA

Note (1) LED light bar input voltage and current are measured by utilizing a true RMS multimeter as shown below:

Note (2) $P_{BL} = I_{PIN} \times V_{PIN} \times$ (14) input pins , LED light bar circuit is (11)Series, (14)Parallel.

Note (3) The lifetime of LED is defined as the time when LED packages continue to operate under the conditions at Ta = 25 ±2 ℃ and I= (20)mA (per chip) until the brightness becomes $\leq$ 50% of its original value.

Version 2.3

Approval

3.3 LIGHTBAR Connector Pin Assignment

Connector: 91500-01001-H01 (Aces)

● Input Connector pin assignment:

(1) Input connector pin assignment: CN1

Input connector CN1		Comments
(vendor) (Aces)	(type) 91500-01001-H01	
Pin	Function	
1	VLED (29.7V)	Input voltage Power Supply + (29.7V.typ)
2	VLED (29.7V)	Input voltage Power Supply + (29.7V.typ)
3	NC	No connect
4	NC	No connect
5	LED1	LED1 negative polarity
6	LED2	LED2 negative polarity
7	LED3	LED3 negative polarity
8	LED4	LED4 negative polarity
9	LED5	LED5 negative polarity
10	LED6	LED6 negative polarity

(2) Input connector pin assignment: CN2

Input connector CN2		Comments
(vendor) (Aces)	(type) 91500-01001-H01	
Pin	Function	
1	LED7	LED7 negative polarity
2	LED8	LED8 negative polarity
3	LED9	LED9 negative polarity
4	LED10	LED10 negative polarity
5	LED11	LED11 negative polarity
6	LED12	LED12 negative polarity
7	NC	No connect
8	NC	No connect
9	VLED (29.7V)	Input voltage Power Supply + (29.7V.typ)
10	VLED (29.7V)	Input voltage Power Supply + (29.7V.typ)

Version 2.3

Approval

4. BLOCK DIAGRAM
4.1 TFT LCD MODULE

Version 2.3

Doc No.: 400032626
Issued Date: Dec. 31, 2009
Model No.: M220Z3-L07

Approval

5. INPUT TERMINAL PIN ASSIGNMENT

5.1 TFT LCD MODULE

Pin	Name	Description
1	RXO0-	Negative LVDS differential data input. Channel O0 (odd)
2	RXO0+	Positive LVDS differential data input. Channel O0 (odd)
3	RXO1-	Negative LVDS differential data input. Channel O1 (odd)
4	RXO1+	Positive LVDS differential data input. Channel O1 (odd)
5	RXO2-	Negative LVDS differential data input. Channel O2 (odd)
6	RXO2+	Positive LVDS differential data input. Channel O2 (odd)
7	GND	Ground
8	RXOC-	Negative LVDS differential clock input. (odd)
9	RXOC+	Positive LVDS differential clock input. (odd)
10	RXO3-	Negative LVDS differential data input. Channel O3(odd)
11	RXO3+	Positive LVDS differential data input. Channel O3 (odd)
12	RXE0-	Negative LVDS differential data input. Channel E0 (even)
13	RXE0+	Positive LVDS differential data input. Channel E0 (even)
14	GND	Ground
15	RXE1-	Negative LVDS differential data input. Channel E1 (even)
16	RXE1+	Positive LVDS differential data input. Channel E1 (even)
17	GND	Ground
18	RXE2-	Negative LVDS differential data input. Channel E2 (even)
19	RXE2+	Positive LVDS differential data input. Channel E2 (even)
20	RXEC-	Negative LVDS differential clock input. (even)
21	RXEC+	Positive LVDS differential clock input. (even)
22	RXE3-	Negative LVDS differential data input. Channel E3 (even)
23	RXE3+	Positive LVDS differential data input. Channel E3 (even)
24	GND	Ground
25	NC	For LCD internal use only, Do not connect
26	NC	For LCD internal use only, Do not connect
27	NC	For LCD internal use only, Do not connect
28	VCC	+5.0V power supply
29	VCC	+5.0V power supply
30	VCC	+5.0V power supply

Note (1) Connector Part No.: 093G30-B0001A(STARCONN) or MSAKT2407P30HA (STM)or

FI-X30SSLH-HF(JAE)

Note (2) Mating Wire Cable Connector Part No.: FI-X30H(JAE) or FI-X30HL(JAE)

Note (3) Mating FFC Cable Connector Part No.: 91500-01001-H01(ACES)

Note (4) The first pixel is odd.

Note (5) Input signal of even and odd clock should be the same timing.

Version 2.3

Approval

LVDS DATA MAPPING TABLE

SELLVDS = Low or Open								
LVDS Channel E0	LVDS output	D7	D6	D4	D3	D2	D1	D0
	Data order	EG0	ER5	ER4	ER3	ER2	ER1	ER0
LVDS Channel E1	LVDS output	D18	D15	D14	D13	D12	D9	D8
	Data order	EB1	EB0	EG5	EG4	EG3	EG2	EG1
LVDS Channel E2	LVDS output	D26	D25	D24	D22	D21	D20	D19
	Data order	DE	NA	NA	EB5	EB4	EB3	EB2
LVDS Channel E3	LVDS output	D23	D17	D16	D11	D10	D5	D27
	Data order	NA	EB7	EB6	EG7	EG6	ER7	ER6
LVDS Channel O0	LVDS output	D7	D6	D4	D3	D2	D1	D0
	Data order	OG0	OR5	OR4	OR3	OR2	OR1	OR0
LVDS Channel O1	LVDS output	D18	D15	D14	D13	D12	D9	D8
	Data order	OB1	OB0	OG5	OG4	OG3	OG2	OG1
LVDS Channel O2	LVDS output	D26	D25	D24	D22	D21	D20	D19
	Data order	DE	NA	NA	OB5	OB4	OB3	OB2
LVDS Channel O3	LVDS output	D23	D17	D16	D11	D10	D5	D27
	Data order	NA	OB7	OB6	OG7	OG6	OR7	OR6

Version 2.3

Approval

5.2 COLOR DATA INPUT ASSIGNMENT

The brightness of each primary color (red, green and blue) is based on the 8-bit gray scale data input for the color. The higher the binary input, the brighter the color. The table below provides the assignment of color versus data input.

Color		Data Signal																								
		Red								Green								Blue							
		R7	R6	R5	R4	R3	R2	R1	R0	G7	G6	G5	G4	G3	G2	G1	G0	B7	B6	B5	B4	B3	B2	B1	B0
Basic Colors	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Green	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
	Cyan	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
	Magenta	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Gray Scale Of Red	Red(0) / Dark	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red(1)	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red(2)	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	Red(253)	1	1	1	1	1	1	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red(254)	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red(255)	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Gray Scale Of Green	Green(0) / Dark	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Green(1)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0
	Green(2)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	Green(253)	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	1	0	0	0	0	0	0	0	0
	Green(254)	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0
	Green(255)	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
Gray Scale Of Blue	Blue(0) / Dark	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Blue(1)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
	Blue(2)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	Blue(253)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	1
	Blue(254)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	0
	Blue(255)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1

Note (1) 0: Low Level Voltage, 1: High Level Voltage

**Version 2.3**

Approval

6. INTERFACE TIMING

6.1 INPUT SIGNAL TIMING SPECIFICATIONS

The input signal timing specifications are shown as the following table and timing diagram.

Signal	Item	Symbol	Min.	Typ.	Max.	Unit	Note
LVDS Clock	Frequency	Fc	49	60	76	MHz	-
	Period	Tc	13	16.7	20	ns	
	Input cycle to cycle jitter	T_{rcl}	-	-	200	ps	(1)
	Spread spectrum modulation range	F_{clkin_mod}	$F_{clkin\_}$-2%	-	$F_{clkin\_}$+2%	MHz	(2)
	Spread spectrum modulation frequency	F_{SSM}	-	-	200	KHz	
	High Time	Tch	-	4/7	-	Tc	-
	Low Time	Tcl	-	3/7	-	Tc	-
LVDS Data	Setup Time	Tlvs	600	-	-	ps	(3)
	Hold Time	Tlvh	600	-	-	ps	
Vertical Active Display Term	Frame Rate	Fr	50	60	75	Hz	Tv=Tvd+Tvb
	Total	Tv	1077	1080	1090	Th	-
	Display	Tvd	1050	1050	1050	Th	-
	Blank	Tvb	Tv-Tvd	30	Tv-Tvd	Th	-
Horizontal Active Display Term	Total	Th	910	920	929	Tc	Th=Thd+Thb
	Display	Thd	840	840	840	Tc	-
	Blank	Thb	Th-Thd	80	Th-Thd	Tc	-

Note: Because this module is operated by DE only mode, Hsync and Vsync input signals are ignored.

INPUT SIGNAL TIMING DIAGRAM

Version 2.3

Approval

Note (1) The input clock cycle-to-cycle jitter is defined as below figures. Trcl = I T_1 – TI


Note (2) The SSCG (Spread spectrum clock generator) is defined as below figures.


Note (3) The LVDS timing diagram and setup/hold time is defined and showing as the following figures.

<u>LVDS RECEIVER INTERFACE TIMING DIAGRAM</u>

16 / 28

Version 2.3

Doc No.: 400032626
Issued Date: Dec. 31, 2009
Model No.: M220Z3-L07

Approval

6.2 POWER ON/OFF SEQUENCE

To prevent a latch-up or DC operation of LCD module, the power on/off sequence should follow the conditions shown in the following diagram.

Timing Specifications:

$0.5 < t1 \leqq 10$ msec

$0 < t2 \leqq 50$ msec

$0 < t3 \leqq 50$ msec

$t4 \geqq 500$ msec

$t5 \geqq 450$ msec

$t6 \geqq 90$ msec

$5 \leqq t7 \leqq 100$ msec

Note.

(1) The supply voltage of the external system for the module input should be the same as the definition of Vcc.

(2) When the backlight turns on before the LCD operation of the LCD turns off, the display may momentarily become abnormal screen.

(3) In case of VCC = off level, please keep the level of input signals on the low or keep a high impedance.

(4) T4 should be measured after the module has been fully discharged between power on/off periods.

(5) Interface signal shall not be kept at high impedance when the power is on.

(6) CMO won't take any responsibility for the products which are damaged by the customers not following the Power Sequence.

(7) There might be slight electronic noise when LCD is turned off (even backlight unit is also off). To avoid this symptom, we suggest "Vcc falling timing" to follow "t7 spec".

Version 2.3

Approval

7. OPTICAL CHARACTERISTICS

7.1 TEST CONDITIONS

Item	Symbol	Value	Unit
Ambient Temperature	Ta	25±2	°C
Ambient Humidity	Ha	50±10	%RH
Supply Voltage	V_{CC}	5	V
Input Signal	According to typical value in "3. ELECTRICAL CHARACTERISTICS"		
LED Light Bar Input Current Per Input Pin	I_{PIN}	20 ± 0.6	mA_{DC}
PWM Duty Ratio	D	100	%
LED Light Bar Test Converter	CMO 27-D041745		

7.2 OPTICAL SPECIFICATIONS

The relative measurement methods of optical characteristics are shown in 7.2. The following items should

be measured under the test conditions described in 7.1 and stable environment shown in Note (5).

Item		Symbol	Condition	Min.	Typ.	Max.	Unit	Note
Color Chromaticity (CIE 1931)	Red	Rx	$\theta_x=0°$, $\theta_Y=0°$ CS-2000	Typ - 0.03	0.636	Typ + 0.03	-	(1), (5)
		Ry			0.345			
	Green	Gx			0.332			
		Gy			**0.617**			
	Blue	Bx			0.156			
		By			0.061			
	White	Wx			0.313			
		Wy			0.329			
Center Luminance of White (Center of Screen)		L_C		200	250	-	cd/m^2	(4), (5)
Contrast Ratio		CR		700	1000	-	-	(2), (5)
Response Time		T_R	$\theta_x=0°$, $\theta_Y=0°$	-	1.3	3.2	ms	(3)
		T_F		-	3.7	6.8		
White Variation		δW	$\theta_x=0°$, $\theta_Y=0°$ USB2000	-	1.3	1.5	-	(5), (6)
Viewing Angle	Horizontal	θ_x+	CR $\geqq$ 10 USB2000	75	85	-	Deg.	(1), (5)
		θ_x-		75	85	-		
	Vertical	θ_Y+		70	80	-		
		θ_Y-		70	80	-		
	Horizontal	θ_x+	CR $\geqq$ 5 USB2000	80	89	-	Deg.	
		θ_x-		80	89	-		
	Vertical	θ_Y+		75	85	-		
		θ_Y-		75	85	-		

Version 2.3

Approval

Note (1) Definition of Viewing Angle (θx, θy):

Note (2) Definition of Contrast Ratio (CR):

The contrast ratio can be calculated by the following expression.

Contrast Ratio (CR) = L255 / L0

L255: Luminance of gray level 255

L 0: Luminance of gray level 0

CR = CR (1)

CR (X) is corresponding to the Contrast Ratio of the point X at Figure in Note (6).

Note (3) Definition of Response Time (T_R, T_F):


Note (4) Definion of Luminance of White (L_C):

Measure the luminance of gray level 255 at center point

L_C = L (1)

L (x) is corresponding to the luminance of the point X at Figure in Note (6).

Version 2.3

Note (5) Measurement Setup:

The LCD module should be stabilized at given temperature for 20 minutes to avoid abrupt temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting Backlight for 20 minutes in a windless room.

Note (6)   Definition of White Variation (δW):

Measure the luminance of gray level 255 at 9 points

δW = Maximum [L (1) ~ L (9)] / Minimum [L (1) ~ L (9)]

Version 2.3

Approval

8. PACKAGING

8.1 PACKING SPECIFICATIONS

(1) 11 LCD modules / 1 Box

(2) Box dimensions: 570(L) X 300 (W) X 430 (H) mm

(3) Weight: 27.87 Kg (11 modules per box)

8.2 PACKING METHOD

(1) Carton Packing should have no failure in the following reliability test items.

| Test Item	Test Conditions	Note
Vibration	ISTA STANDARD Random, Frequency Range: 1 – 200 Hz Top & Bottom: 30 minutes (+Z), 10 min (-Z), Right & Left: 10 minutes (X) Back & Forth 10 minutes (Y)	Non Operation
Dropping Test	1 Corner, 3 Edge, 6 Face, 30.5cm, (ISTA STANDARD)	Non Operation

Figure. 8-1 Packing method

Version 2.3

Approval

For ocean shipping

Figure. 8-2 Packing method

For air transport

Figure. 8-3 Packing method

Version 2.3

Doc No.: 400032626
Issued Date: Dec. 31, 2009
Model No.: M220Z3-L07

Approval

## 9. DEFINITION OF LABELS

9.1 CMO MODULE LABEL

The barcode nameplate is pasted on each module as illustration, and its definitions are as following explanation.

(a) Model Name: M220Z3-L07

(b) Revision: Rev. XX, for example: A0, A1… B1, B2… or C1, C2…etc.

(c) CMO barcode definition:

Serial ID: XX-XX-X-XX-YMD-L-NNNN

Code	Meaning	Description
XX	CMO internal use	-
XX	Revision	Cover all the change
X	CMO internal use	-
XX	CMO internal use	-
YMD	Year, month, day	Year: 0~9, 2001=1, 2002=2, 2003=3…2010=0, 2011=1, 2012=2… Month: 1~12=1, 2, 3, ~, 9, A, B, C Day: 1~31=1, 2, 3, ~, 9, A, B, C, ~, W, X, Y, exclude I, O, and U.
L	Product line #	Line 1=1, Line 2=2, Line 3=3, …
NNNN	Serial number	Manufacturing sequence of product

(d) Customer's barcode definition:

Serial ID: CM-22Z37-X-X-X-XX-L-XX-L-YMD-NNNN

Code	Meaning	Description
CM	Supplier code	CMO=CM
22Z37	Model number	M220Z3-L07=22Z37
X	Revision code	Non ZBD: 1,2,~,8,9 / ZBD: A~Z
X	Source driver IC code	Century=1, CLL=2, Demos=3, Epson=4, Fujitsu=5, Himax=6, Hitachi=7, Hynix=8, LDI=9, Matsushita=A, NEC=B, Novatec=C,
X	Gate driver IC code	OKI=D, Philips=E, Renasas=F, Samsung=G, Sanyo=H, Sharp=I, TI=J, Topro=K, Toshiba=L, Windbond=M
XX	Cell location	Tainan, Taiwan=TN
L	Cell line #	1,2,~,9,A,B,~,Y,Z
XX	Module location	Tainan, Taiwan=TN ; Ningbo China=NP
L	Module line #	1,2,~,9,A,B,~,Y,Z
YMD	Year, month, day	Year: 0~9, 2001=1, 2002=2, 2003=3…2010=0, 2011=1, 2012=2… Month: 1~12=1, 2, 3, ~, 9, A, B, C Day: 1~31=1, 2, 3, ~, 9, A, B, C, ~, T, U, V
NNNN	Serial number	By LCD supplier

(e) UL Factory ID:

Region	Factory ID
TWCMO	GEMN
NBCMO	LEOO
NBCME	CANO
NHCMO	CAPG

Version 2.3

CHI MEI
OPTOELECTRONICS CORP.

Approval

10.Reliability Test

Environment test conditions are listed as following table.

Items	Required Condition	Note
Temperature Humidity Bias (THB)	Ta= 50℃ , 80%RH, 240hours	
High Temperature Operation (HTO)	Ta= 50℃ , 50%RH , 240hours	
Low Temperature Operation (LTO)	Ta= 0℃ , 240hours	
High Temperature Storage (HTS)	Ta= 60℃ , 240hours	
Low Temperature Storage (LTS)	Ta= -20℃ , 240hours	
Vibration Test (Non-operation)	Acceleration: 1.5 Grms Wave: Half-sine Frequency: 10 - 300 Hz Sweep: 30 Minutes each Axis (X, Y, Z)	
Shock Test (Non-operation)	Acceleration: 50 G Wave: Half-sine Active Time: 11 ms Direction : ± X, ± Y, ± Z.(one time for each Axis)	
Thermal Shock Test (TST)	-20℃/30min , 60℃ / 30min , 100 cycles	
On/Off Test	25℃ ,On/10sec , Off /10sec , 30,000 cycles	
ESD (Electro Static Discharge)	Contact Discharge: ± 8KV, 150pF(330Ω)	
	Air Discharge: ± 15KV, 150pF(330Ω)	
Altitude Test	Operation:10,000 ft / 24hours Non-Operation:30,000 ft / 24hours	

Version 2.3

11. PRECAUTIONS

11.1 ASSEMBLY AND HANDLING PRECAUTIONS

(1) Do not apply rough force such as bending or twisting to the module during assembly.

(2) To assemble or install module into user's system can be only in clean working areas. The dust and oil may cause electrical short or worsen the polarizer.

(3) It's not permitted to have pressure or impulse on the module because the LCD panel and Backlight will be damaged.

(4) Always follow the correct power sequence when LCD module is connecting and operating. This can prevent damage to the CMOS LSI chips during latch-up.

(5) Do not pull the I/F connector in or out while the module is operating.

(6) Do not disassemble the module.

(7) Use a soft dry cloth without chemicals for cleaning, because the surface of polarizer is very soft and easily scratched.

(8) It is dangerous that moisture come into or contacted the LCD module, because moisture may damage LCD module when it is operating.

(9) High temperature or humidity may reduce the performance of module. Please store LCD module within the specified storage conditions.

(10) When ambient temperature is lower than 10ºC may reduce the display quality. For example, the response time will become slowly.

11.2 SAFETY PRECAUTIONS

(1) If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth. In case of contact with hands, skin or clothes, it has to be washed away thoroughly with soap.

(2) After the module's end of life, it is not harmful in case of normal operation and storage.

11.3 SAFETY STANDARDS

The LCD module should be certified with safety regulations as follows:

(1) UL60950-1 or updated standard.

(2) IEC60950-1 or updated standard.

11.4. Storage

(1) Do not leave the module in high temperature, and high humidity for a long time.

It is highly recommended to store the module with temperature from 0℃ to 35℃

And relative humidity of less than 70%

(2) Do not store the TFT – LCD module in direct sunlight

(3) The module should be stored in dark place. It is prohibited to apply sunlight or fluorescent light in storing

Version 2.3

Doc No.: 400032626
Issued Date: Dec. 31, 2009
Model No.: M220Z3-L07

Approval

11.5. Operation condition guide

(1)   The LCD product should be operated under normal condition.

Normal condition is defined as below :

Temperature : 20±15℃

Humidity: 65±20%

Display pattern : continually changing pattern(Not stationary)

(2)   If the product will be used in extreme conditions such as high temperature , high humidity , high altitude , display pattern or operation time etc…It is strongly recommended to contact CMO for application engineering advice . Otherwise , Its reliability and function may not be guaranteed.

11.6 OTHER

When fixed patterns are displayed for a long time, remnant image is likely to occur.

12. MECHANICAL CHARACTERISTICS

[Refer to the next 2 pages]

Version 2.3

Active Area 473.76*296.1

493.7 ±0.5 (OUTLINE)

352.1 ±0.5 (OUTLINE)

300.1 ±0.3 (OPEN AREA)

477.7 ±0.3 (OPEN AREA)

(197)

(197)

(2)

(2)

8

10

GAP Max. 0.5mm

10 ±0.5

4-5.6 ±0.3

28.05 ±0.3

56 ±0.3

152 ±0.3

56 ±0.3

10 ±0.5

4-5.6 ±0.3

12 ±0.3

12 ±0.3

28.05 ±0.3

240 ±0.3

12 ±0.3

175.85 ±1

47.1 ±1

(112.9)

Z=7.22

Z=6.92

(71)